

Introduction to Quantum Information Processing

CS 467 / CS 667

Phys 467 / Phys 767

C&O 481 / C&O 681

Lecture 16 (2005)

Richard Cleve

DC 3524

cleve@cs.uwaterloo.ca

Course web site at:

<http://www.cs.uwaterloo.ca/~cleve/courses/cs467>

Contents

- Preliminary remarks about quantum communication
- The GHZ “paradox”
- The Bell inequality and its violation
 - Physicist’s perspective
 - Computer Scientist’s perspective
- The magic square game

- Preliminary remarks about quantum communication
- The GHZ “paradox”
- The Bell inequality and its violation
 - Physicist’s perspective
 - Computer Scientist’s perspective
- The magic square game



Quantum information can apparently be used to substantially reduce ***computation*** costs for a number of interesting problems

How does quantum information affect the ***communication costs*** of information processing tasks?

We explore this issue ...

Entanglement and signaling

Recall that Entangled states, such as $\frac{1}{\sqrt{2}}|00\rangle + \frac{1}{\sqrt{2}}|11\rangle$,



can be used to perform some intriguing feats, such as *teleportation* and *superdense coding*

—but they **cannot** be used to “signal instantaneously”

Any operation performed on one system has no affect on the state of the other system (its reduced density matrix)

Basic communication scenario

Goal: convey n bits from Alice to Bob



Basic communication scenario

Bit communication:




Cost: n

Qubit communication:




Cost: n [Holevo's Theorem, 1973]

Bit communication
& prior entanglement:



Cost: n (can be deduced)

Qubit communication
& prior entanglement:




Cost: $n/2$ superdense coding
[Bennett & Wiesner, 1992]

- Preliminary remarks about quantum communication
- The GHZ “paradox”
- The Bell inequality and its violation
 - Physicist’s perspective
 - Computer Scientist’s perspective
- The magic square game

GHZ scenario

[Greenberger, Horne, Zeilinger, 1980]

Input:



r



s



t

Output:

Alice

a

$$a \leftarrow r$$

Bob

b

$$b \leftarrow \neg s$$

Carol

c

$$c \leftarrow 1$$


Rules of the game:

1. It is promised that $r \oplus s \oplus t = 0$
2. No communication after inputs received
3. They **win** if $a \oplus b \oplus c = r \vee s \vee t$



rst	$a \oplus b \oplus c$	abc
000	0	011
011	1	001
101	1	111
110	1	101

No perfect strategy for GHZ



rst	$a \oplus b \oplus c$
000	0
011	1
101	1
110	1

Has no solution,
thus no perfect
strategy exists


General deterministic strategy:

$$a_0, a_1, b_0, b_1, c_0, c_1$$

Winning conditions:

$$\left\{ \begin{array}{l} a_0 \oplus b_0 \oplus c_0 = 0 \\ a_0 \oplus b_1 \oplus c_1 = 1 \\ a_1 \oplus b_0 \oplus c_1 = 1 \\ a_1 \oplus b_1 \oplus c_0 = 1 \end{array} \right.$$

GHZ: preventing communication






Input and output events can be **space-like** separated:
so signals at the speed of light are not fast enough for cheating

What if Alice, Bob, and Carol **still** keep on winning?

“GHZ Paradox” explained

Prior entanglement: $|\psi\rangle = |000\rangle - |011\rangle - |101\rangle - |110\rangle$



Alice's strategy:

1. if $r = 1$ then apply H to qubit
2. measure qubit and set a to result

$$H = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$$

Bob's & Carol's strategies: similar

Case 1 ($rst = 000$): state is measured directly $\dots |000\rangle + |010\rangle - |100\rangle + |111\rangle$ 😊

Cases 3 & 4 ($rst = 101$ & 110): similar by symmetry 😊

GHZ: conclusions

- For the GHZ game, any *classical* team succeeds with probability at most $\frac{3}{4}$
- Allowing the players to communicate would enable them to succeed with probability 1
- Entanglement cannot be used to communicate
- Nevertheless, allowing the players to have entanglement enables them to succeed with probability 1
- Thus, entanglement is a useful resource for the task of *winning the GHZ game*


- Preliminary remarks about quantum communication
- The GHZ “paradox”
- The Bell inequality and its violation
 - Physicist’s perspective
 - Computer Scientist’s perspective
- The magic square game

Bell's Inequality and its violation

Part I: physicist's view:

Can a quantum state have *pre-determined* outcomes for each possible measurement that can be applied to it?

qubit:



where the “manuscript”
is something like this:

called *hidden variables*

if $\{|0\rangle, |1\rangle\}$ measurement
then output **0**

if $\{|+\rangle, |-\rangle\}$ measurement
then output **1**

if ... (etc)


table could be implicitly
given by some formula

[Bell, 1964]

[Clauser, Horne, Shimony, Holt, 1969]

Bell Inequality

Imagine a two-qubit system, where one of two measurements, called M_0 and M_1 , will be applied to each qubit:



Define:

$$A_0 = (-1)^{a_0}$$

$$A_1 = (-1)^{a_1}$$

$$B_0 = (-1)^{b_0}$$

$$B_1 = (-1)^{b_1}$$

Claim: $A_0 B_0 + A_0 B_1 + A_1 B_0 - A_1 B_1 \leq 2$

Proof: $A_0 (B_0 + B_1) + A_1 (B_0 - B_1) \leq 2$

↑ ↑
one is ± 2 and the other is 0

Bell Inequality

$A_0 B_0 + A_0 B_1 + A_1 B_0 - A_1 B_1 \leq 2$ is called a **Bell Inequality***

Question: could one, in principle, design an experiment to check if this Bell Inequality holds for a particular system?


Answer 1: no, not directly, because A_0, A_1, B_0, B_1 cannot all be measured (only **one** $A_s B_t$ term can be measured)

Answer 2: yes, indirectly, by making many runs of this experiment: pick a random $st \in \{00, 01, 10, 11\}$ and then measure with M_s and M_t to get the value of $A_s B_t$

The **average** of $A_0 B_0, A_0 B_1, A_1 B_0, -A_1 B_1$ should be $\leq \frac{1}{2}$


* also called CHSH Inequality

Violating the Bell Inequality



Two-qubit system in state

$$|\phi\rangle = |00\rangle - |11\rangle$$



Applying rotations θ_A and θ_B yields:


$$\underbrace{\cos(\theta_A + \theta_B)}_{AB = +1} (|00\rangle - |11\rangle) + \underbrace{\sin(\theta_A + \theta_B)}_{AB = -1} (|01\rangle + |10\rangle)$$

Define

M_0 : rotate by $-\pi/16$ then measure

M_1 : rotate by $+3\pi/16$ then measure


Then $A_0 B_0$, $A_0 B_1$, $A_1 B_0$, $-A_1 B_1$ all have expected value $\frac{1}{2}\sqrt{2}$, which **contradicts** the upper bound of $\frac{1}{2}$



Bell Inequality violation: summary

Assuming that quantum systems are governed by *local hidden variables* leads to the Bell inequality

$$A_0 B_0 + A_0 B_1 + A_1 B_0 - A_1 B_1 \leq 2$$



But this is *violated* in the case of Bell states (by a factor of $\sqrt{2}$)

Therefore, no such hidden variables exist

This is, in principle, experimentally verifiable, and experiments along these lines have actually been conducted





- Preliminary remarks about quantum communication
- The GHZ “paradox”
- The Bell inequality and its violation
 - Physicist’s perspective
 - Computer Scientist’s perspective
- The magic square game

Bell's Inequality and its violation

Part II: computer scientist's view:

input:



output:

- Rules:**
1. No communication after inputs received
 2. They *win* if $a \oplus b = s \wedge t$



st	$a \oplus b$
00	0
01	0
10	0
11	1

With classical resources, $\Pr[a \oplus b = s \wedge t] \leq 0.75$

But, with prior entanglement state $|00\rangle - |11\rangle$,

$\Pr[a \oplus b = s \wedge t] = \cos^2(\pi/8) = \frac{1}{2} + \frac{1}{4}\sqrt{2} = 0.853\dots$


The quantum strategy

- Alice and Bob start with entanglement

$$|\phi\rangle = |00\rangle - |11\rangle$$

- **Alice:** if $s = 0$ then rotate by $\theta_A = -\pi/16$ else rotate by $\theta_A = +3\pi/16$ and measure

- **Bob:** if $t = 0$ then rotate by $\theta_B = -\pi/16$ else rotate by $\theta_B = +3\pi/16$ and measure




$$\cos(\theta_A - \theta_B) (|00\rangle - |11\rangle) + \sin(\theta_A - \theta_B) (|01\rangle + |10\rangle)$$

Success probability:

$$\Pr[a \oplus b = s \wedge t] = \cos^2(\pi/8) = \frac{1}{2} + \frac{1}{4}\sqrt{2} = 0.853\dots$$

Nonlocality in operational terms



- Preliminary remarks about quantum communication
- The GHZ “paradox”
- The Bell inequality and its violation
 - Physicist’s perspective
 - Computer Scientist’s perspective
- The magic square game

Magic square game

Problem: fill in the matrix with bits such that each row has even parity and each column has odd parity

a_{11}	a_{12}	a_{13}	even
a_{21}	a_{22}	a_{23}	even
a_{31}	a_{32}	a_{33}	even
odd	odd	odd	

IMPOSSIBLE

		orange
teal	teal	purple
		orange

Game: ask Alice to fill in one row and Bob to fill in one column

They *win* iff parities are correct and bits agree at intersection


Success probabilities: $8/9$ classical and 1 quantum

Preview of communication complexity


Classical Communication Complexity

[Yao, 1979]

$x_1 x_2 \dots x_n$



$y_1 y_2 \dots y_n$



$f(x, y)$


E.g. equality function: $f(x, y) = 1$ if $x = y$, and 0 if $x \neq y$

Any **deterministic** protocol requires n bits communication


Probabilistic protocols can solve with only $O(\log(n/\epsilon))$ bits communication (error probability ϵ)

Quantum Communication Complexity

Qubit communication



Prior entanglement



Question: can quantum beat classical in this context?

THE END

The text 'THE END' is rendered in a bold, italicized, sans-serif font. The letters are a dark grey color. Below the text, there are several parallel, gold-colored lines that create a sense of depth and shadow, making the text appear to be floating above a surface.